

# Traglasten Hauptausleger

## mit minimaler Abstützbasis

### 506-5.1



7,7 - 16,9 m









4,7 x 4,1 m



360°

DIN

 m	Auslegerlänge / Rollenkopfhöhe				
	6,2 / 7,7 m 	8,4 / 10,2 m 	10,9 / 12,6 m 	13,3 / 14,7 m 	15,7 / 16,9 m 
2,0 2,5 3,0	3,00 3,00 3,00	3,00			
3,5 4,0 4,5	3,00 2,40 2,00	3,00 2,40 2,00	2,00 1,80		
5,0 5,5 6,0	1,65 1,35 1,10	1,65 1,35 1,10	1,60 1,35 1,10	1,00 0,92 0,85	0,50
6,6 7,0 7,5		0,90 0,75 0,60	0,90 0,75 0,65	0,75 0,70 0,60	0,45 0,40 0,35
8,0 8,5 9,0		0,50 0,45	0,50 0,45 0,40	0,50 0,45 0,40	0,35 0,33 0,30
10,0 10,7 12,0			0,30	0,30 0,25 0,20	0,25 0,23 0,20
13,0 14,0 15,4				0,17	0,16 0,15 0,10



Hakenflasche 3-rollig

Traglasten (t)